



Labels that Last

119 Matte Silver "VOID" Tamper-Evident Polyester

Description: This material is ideal for property, asset, and equipment marking where durable, moisture, heat & solvent resistant bar code labeling is needed. If there is any attempt to remove these labels from an application surface, the aggressive adhesive will fracture leaving the word "VOID" on the applied surface. * The label is rendered useless by becoming clear in the "VOID" areas. We must note however, that this tamper evidence feature becomes non-functional if the label is exposed to temperatures above 104°F (40°C).

It prints well with impact and dot matrix printers as well as with thermal transfer printers using wax/resin ribbons. For good barcode scanning and where additional durability is needed, a matte over laminate film is recommended.

Recommended EIM Ribbons: T96, T68 Resin or T58 wax/resin

Compliance: UL Recognized (PDGJ12 / 8) when printed with T38, T46, T68 or T80 ribbons.
RoHS and REACH SVHC Compliant

	Face Stock	Adhesive	Liner
Type	Polyester	Permanent Acrylic	Silicone Paper
Color	Matte Silver	-	-
Caliper	2.5 mil (65 micron)	0.8 - 0.9 mil (20 - 23 micron) +/- 10%	3.1 mil (79 micron) +/- 10%
Basis Weight	-	-	50#
Min. Application Temp.	-	32°F (0°C)	-
Service Temp. Range	-	-40°F to 302°F (-40°C to 150°C)	-

	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	72°F (21°C)	50% R.H.	One Year

Please allow 24-48 hours for your labels to setup before testing for tamper evidence. The tamper evident features of this product will become permanently non-functional if it is exposed to temperatures above 104°F (40°C).

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.

Test it yourself with free samples! Visit barcode-labels.com/get-samples/