



Labels that Last

202 Direct Thermal Paper

Description: This general-purpose, smooth white paper has medium sensitivity for standard speed thermal printers. and is particularly popular in weigh-scale applications. It has a special topcoating that protects the thermal layer to maximize printhead life. It is also resistant to oils, fats, blood, and plasticizers found in PVC, as well as alcohol, solvents and vinegar.

It has a versatile, all-purpose adhesive for excellent bonding to corrugated, glass and plastics.

The liner has high strength and tear resistance.

Compliance: FDA 21 CFR 175.105 for Indirect Food Contact

	Face Stock	Adhesive	Liner
Type	Paper	Permanent Acrylic	Bleached Kraft
Color	White	-	-
Caliper	3.2 mil +/- 10%	0.80 mil +/- 10%	2.47 mil +/- 10%
Basis Weight	53.5# (25 x 38 shts)	-	41.5# (24 x 36 shts)
Min. Application Temp.	-	30°F (-1°C)	-
Service Temp. Range	-	-65°F to 200°F (-53°C to 93°C)	-
	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	72°F (22°C)	50% R.H.	One Year

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.

Test it yourself with free samples! Visit barcode-labels.com/get-samples/