



# Labels that Last

## 310 Paper with High Tack Adhesive

**Description:** This ultra-smooth coated bright white paper provides excellent print results for barcodes and fine text. It offers good smudge-resistance in all kinds of thermal transfer printers.

The "quick-stick", aggressive adhesive handles a variety of temperature requirements and is excellent for applications such as shipping labels that need to be applied to packaging films or substrates like glass, metal, plastic, and wood. The liner has high internal strength and tear resistance.

**Compliance:** FDA 21 CFR 175.105 for indirect food contact.

**Recommended Printing Ribbons:** T38 Wax, T44 Wax/Resin

	Face Stock	Adhesive	Liner
Type	Paper	Hot Melt Rubber	Bleach Coated Kraft
Color	White	-	-
Caliper	3.2 mil	0.9 mil	2.5 mil
Basis Weight	59#/ream (25 x 38)	-	41#/ream (24 x 36)
Min. Application Temp.	-	40°F (4°C)	-
Service Temp. Range	-	-65°F to 160°F (-53°C to 71°C)	-

	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	72°F	50% R.H.	One Year

**NOTE:** Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.