



Labels that Last

444 Semi-Gloss Silver Polyester

Description: This Semi-Gloss silver polyester has a special gloss coating that allows for high quality barcode printing and easy scanning. It comes with a high performance adhesive that works very well on glass, metals, and high surface energy plastics. It is UL Recognized for Indoor/Outdoor use with occasional exposure to lubricating oil and water. It has an expected exterior life of two years.

UL Recognized:

Marking & Labeling Systems PDGQ2 See EIM UL File #MH48554 for printed labels.

Marking & Labeling Components PDGJ12 - See EIM UL File # MH27790 for label materials.

Recommended Ribbons: T68, T80, T84, T94 (See UL File #MH27790)

Compliance: RoHS and REACH SVHC Candidate List

	Face Stock	Adhesive	Liner
Type	Polyester	Permanent Acrylic	Silicone Paper
Color	Silver	-	-
Caliper	2.0 mil (51 micron) +/- 10%	0.8 - 0.9 mil (20 - 23 micron) +/- 10%	3.1 mil (79 micron) +/- 10%
Basis Weight	-	-	50#
Min. Application Temp.	-	50°F (10°C)	-
Service Temp. Range	-	-40°F to 302°F (-40°C to 150°C)	-

	Temperature Range	Humidity Range	Shelf Life
Recommended Storage Conditions	70°F (10°C)	50% R.H.	Two Years

All descriptive information, typical performance data, and recommendations for this product should be used solely as a guide. Furnishing such information is merely our attempt to assist you as indicated by your requested application. These specifications do not constitute a warranty under any varying results. All labels are sold with the understanding that the purchaser has independently tested and determined the suitability of the product for the intended application.

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.