



Labels that Last

520 White VOID Polyester

Description: This tamper-evident polyester has a ultra-smooth topcoat for fine resolution printing. When attempting to remove this label, its patterned, aggressive adhesive leaves behind a distinct and highly visible “VOID” message.

Common uses include asset tracking and warranty tracking in the automotive, electronics and pharmaceutical markets.

Recommended Printing Ribbons: EIM T84, T68

	Face Stock	Adhesive	Liner
Type	Polyester	Permanent VOID Acrylic*	Kraft Paper
Color	White	-	-
Caliper	2.0 mil (50 micron) +/- 10%	0.10 mil (25 micron) +/- 10%	3.2 mil (80 micron) +/- 10%
Basis Weight	-	-	50#
Min. Application Temp.	-	45°F (7°C)	-
Service Temp. Range	-	-30°F to 300°F (-34°C to 149°C) *	-
Exterior Life	Two Years		

	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	70°F (21°C)	50% R.H.	Two Years

* Please allow 24-48 hours for your labels to setup before testing them for tamper evidence.

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.

Test it yourself with free samples! Visit barcode-labels.com/get-samples/