



Labels that Last

524 White Satin Destructible Vinyl

Description: This fragile, yet resilient thermal transfer label will “fracture” and self-destruct if anyone tries to remove it. It works much like peeling paint, you have to chip at it and it will not come off in one piece. The destructible feature prevents the reuse and re-application of labels. The vinyl face provides resistance to water and cleaning solutions. The adhesive provides aggressive initial tack, excellent adhesion, and is extremely chemical and solvent resistant. Bonds well to various high and low surface energy substrates.

This label is designed for tamper evident labels used in industrial and electronic packaging device identification, warranty and asset protection, automotive VIN labels, and security seals.

Recommended Printing Ribbons: T68, T84, and T98

	Face Stock	Adhesive	Liner
Type	Vinyl	Permanent Acrylic *	White Glassine
Color	White	Clear	White
Caliper	2.0 mil	0.7 mil	2.6 mil
Basis Weight	-	-	50#
Min. Application Temperature	50°F (10°C)		
Service Temp. Range	-40°F to 212°F (-40°C to 100°C)		
	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	72°F (22°C)	50% R.H.	One Year

* Please allow 24-48 hours for your labels to setup before testing for tamper evidence.

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.

Test it yourself with free samples! Visit barcode-labels.com/get-samples/