



Labels that Last

524 White Satin Destructible Vinyl

Description: This fragile, yet resilient thermal transfer label will “fracture” and self-destruct if anyone tries to remove it. It works much like peeling paint, you have to chip at it and it will not come off in one piece. The destructible feature prevents the reuse and re-application of labels. The vinyl face provides water resistance and resistance to cleaning solutions. The adhesive provides aggressive initial tack, excellent adhesion, and is extremely chemical and solvent resistant. The adhesive bonds well to various high and low surface energy substrates.

This label is designed for use for tamper evident labels used in industrial and electronic packaging device identification, warranty & asset protection, automotive VIN labels & security seals.

Recommended Printing Ribbons: T68, T84, & T98

| | Face Stock | Adhesive | Liner |
|------------------------------|---------------------------------|-------------------|----------------|
| Type | Vinyl | Permanent Acrylic | White Glassine |
| Color | White | Clear | White |
| Caliper | 2.0 mil | 0.7 mil | 2.6 mil |
| Basis Weight | - | - | 50# |
| Min. Application Temperature | 50°F (10°C) | | |
| Service Temp. Range | -40°F to 212°F (-40°C to 100°C) | | |

| | Temperature | Humidity | Shelf Life |
|--------------------------------|-------------|----------|------------|
| Recommended Storage Conditions | 72°F | 50% R.H. | One Year |

** Please allow 24-48 hours for your labels to setup before testing for tamper evidence.*

NOTE: Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.