



Labels that Last

602 Matte White Paper

Description: This is a premium ultra matte paper with superior smudge resistance, high brightness, and high opacity. It comes with an all-temperature, glove-friendly adhesive that is suitable for warm- or hot-filling packaging applications. We recommend testing, but this should also work on cold-temp food packaging and corrugated containers.

As additional features, the alkaline-based face sheet meets the ANSI / NISO Spec Z39.48-1992 for libraries and information services. Other archival storage concerns are addressed by the use of an adhesive that meets the PAT (Photo Activity Test) for ISO 14523, which pertains to the pH, lignin content, tear resistance, and alkaline reserve.

Other Compliance: 16 CFR 1500.3 for Oral Toxicity and Skin Irritation
 21 CFR 175.105 for Indirect Food Contact
 21 CFR 801.437 for No Natural Latex or Dried Rubber Content
 CONEG for Toxics in Packaging

Recommended Printing Ribbons: T38/T39 Wax and T44 Wax/Resin

	Face Stock	Adhesive	Liner
Type	Paper	Permanent Acrylic	Bleach Coated Kraft
Color	White	Clear	White
Caliper	3.9 mil	0.6 mil	3.2 mil
Basis Weight	60#(3300 ft ²)	-	51.6#(3000 ft ²)
Tensile MD/CD	35 / 17 # / inch	-	45 / 18 #/inch
Tear MD/CD	50 / 60 grams	-	60 / 60 grams
Opacity	91%		80%
Brightness	89%	-	-
Min. Application Temp.	-	-20°F (-29°C)	-
Service Temp. Range	-	-65°F to 200°F (-54°C to 93°C)	-
Total Caliper	7.7 mil		
	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	72°F (22°C)	50% R.H.	One Year

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.

Test it yourself with free samples! Visit barcode-labels.com/get-samples/