



Labels that Last

787 Polycarbonate FloorCode™ Streamline

Description: This polycarbonate material is specifically designed for floor marking applications where human readable and barcoded information is needed. FloorCode™ Streamline 787 has a clear, velvet finish that reduces glare, and can be cleaned with general purpose cleaners. The strength of polycarbonate protects labels against heavy traffic and yet is thin enough to avoid becoming a tripping hazard.

FloorCode™ Streamline is easy to install, and instructions are also provided. It is important to thoroughly clean the floor with a general purpose cleaner and to let the surface dry. Avoid application over floor seams, joints or other markings that may deteriorate.

For ultimate bonds, we recommend that FloorCode™ Streamline 787 overlays be at least 1/2 inch larger (on all four sides) than the label beneath and that the labels you use also have a very aggressive adhesive. It is important to apply pressure to the laminate (such as using body weight). If you need to remove Floor-Code™ Streamline, simply place a small scraper blade under the laminate strip and pull up at a 180° angle.

If label material is needed, EIM offers white polyester or retro-reflective (for long distance scanning) to pair with the FloorCode™ Streamline. Consult The Label Experts for more information.



	Facestock	Adhesive	Liner
Type	Polycarbonate	Acrylic	Kraft Paper
Color	Velvet Clear	Clear	White
Caliper	5 mil	2 mil	4.3 mil
Min. Application Temp.	-	32°F (0°C)	-
Service Temp. Range	-	-40°F to 212°F (-40°C to 100°C)	-
Total Caliper	12 mil		

	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	70°F(21°C)	50% R.H.	Two Year

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.