



Labels that Last

787 Polycarbonate FloorCode™ Streamline

Description: This polycarbonate material is specifically designed for floor marking applications where human readable and barcoded information is needed. FloorCode Streamline has a clear, velvet finish that reduces glare, and can be cleaned with general purpose cleaners. The strength of polycarbonate protects labels against heavy traffic and yet is thin enough to avoid becoming a tripping hazard.

FloorCode Streamline is easy to install, and instructions are also provided. It is important to thoroughly clean the floor with a general purpose cleaner and to let the surface dry. Avoid application over floor seams, joints or other markings that may deteriorate.

For ultimate bonds, we recommend that FloorCode Streamline overlays be at least 1/2 inch larger (on all four sides) than the label beneath and that the labels you use also have a very aggressive adhesive. It is important to apply pressure to the laminate (such as using body weight). If you need to remove FloorCode Streamline, simply place a small scraper blade under the laminate strip and pull up at a 180° angle.

If label material is needed, EIM offers a white polyester to pair with the FloorCode Streamline. Consult your Label Expert for more information.

	Facestock	Adhesive	Liner
Type	Polycarbonate	Acrylic	Kraft Paper
Color	Velvet Clear	Clear	White
Caliper	5.0 mil	2.0 mil	4.3 mil
Min. Application Temp.	-	32°F (0°C)	-
Service Temp. Range	-	-40°F to 212°F (-40°C to 100°C)	-
Total Caliper	12 mil		

	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	70°F (21°C)	50% R.H.	Two Years

NOTE: Due to the variety of application conditions, Electronic Imaging Materials strongly encourages the end-user to do thorough testing of all label products under consideration to make sure they will meet the application requirements.

Test it yourself with free samples! Visit barcode-labels.com/get-samples/